

PB 1400

Product Type: PolyButene

Performance

- * No Color, no odor and non-toxic
- * Excellent stability of oxidant and UV light
- * Improve the lubricity
- * High purity
- * Very enhancement in solution viscosity
- * Excellent shearing resistance
- * No poisonous residue and lower coke formation
- * Longer oil-drain intervals
- * Extended equipment lifetime
- * Reduced energy consumption
- * usage instead of bright stock

Characteristics:

Item	Unit	Typical	Test Method
Molecular weight	Mn	1400	GPC
Kinematic Viscosity	cSt		ASTM D445
40°C		27000	
100°C		810	
Flash Point (COC)	°C	230	ASTM D92
Density @25°C	g/cm ³	0.899	ASTM D1963
Pour Point	°C	5	ASTM D97
Loss on Heating	% wt	0.10	ASTM D2101
Color	APHA	15	ASTM D1209
Water Content	ppm	30	ASTM D6304
Acid Value	mgKOH/g	0.01	ASTM D974
Sulfur Content	ppm	1	ASTM D2785

Application

- * Hydraulic Fluids
- * Compressor Oils
- * Grease
- * Metal Working Fluids
- * Gear Oils
- * 2-Stroke Engine Oils
- * Transmission Fluids
- * Quench Oil(Accelerated Cooling Brightener)

Dowpol Chemical International Corp.

Add : 4F, No.618 Shangcheng Road, Pudong, Shanghai, China, 200120

Tel : 86 21-58585559 51875599 Fax : 86 21-58585337 58768943

Revision Date April, 2010

©Dowpol Chemical. Products change without prior notice.