

Product Description

PriEco 8004 Phenyl Polycarboxylic Ester are API category Group V fluids. They have excellent high-temperature properties, anti-oxidative stability and low volatilities for high temperature applications.

Features and Benefits

- ★ Excellent high temperature and anti-oxidative stability
- \star Low carbon deposition formation tendency performance
- \star High flash point and ignition temperature
- \star Good low temperature fluidity
- \star Very low evaporation rate
- \star High viscosity index
- ★ Good biodegradability
- \star Good Stabilities of hydrolysis

Typical Properties

Items	PriEco8004	Test Methods
Appearance	Bright & Clear	Visual
Density @20°C, g/cm ³	0.973	ASTM D1298
Kinematic Visscosity,mm ² /s 100 °C 40 °C	8.0 51.7	ASTM D445
Viscosity Index	124	ASTM D2270
Flash Point (COC), °C	282	ASTM D92
Pour Point, °C	-50	ASTM D97
Acid Number, mgKOH/g	0.05	ASTM D974
Color	0.5	ASTM D1500
Water Content, %	0.07	ASTM D1533 Part B
Noack Evaporation Loss, %	0.4	DIN 51581

Application

PriEco 8004 Phenyl Polycarboxylic Esters can be used as sole base stocks or blend stocks with other synthetic fluids in many high temperature industrial lubricant applications. These esters are ideal for use in highly temperature and cleanliness lubricant applications where energy efficiency is desired.

- ★ Compressor Oils
- ★ Grease

- ★ Gear Oils
- ★ Chain Oils

Http://www.nacolube.com **Typical properties: these are not to be construed as specifications** 2011 NACO Lubrication Co., Ltd. All right reserved.

NACO Lubrication Co., Ltd. Synthetics Base Oil Dep.